

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6545)</p> <p>-----</p> <p>Set ¼ sec. post, at average distance, from which A B.Oak 9" dia., bears N.78°W., 21 lks. dist. A B.Oak 12" dia., bears S.10°W., 27 lks. dist.</p>
<p>Douglas Co. Surveyors Office - Frank Cain, May 11, 1913 - Field Book 63 Pgs 52/-56 - C.S. File 6/26</p> <p>-----</p> <p>Set an Oak stake 4" x 4" x 36", 18" in the ground. A Fir 8" dia., N.20°30'E., 30 lks. A W.Oak 36" dia., S.61°45'W., 84 lks.</p>
<p>Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - May/June 1962 - C.S. File 49/139-69</p> <p>-----</p> <p>Found - 1¼" I.P. at corner and both BTs as recorded by Cain. The SW BT, now snag. New BT - 16" Red Fir bears S.2°W., 13.0 ft. scribed ¼ S17 CS BT.</p>
<p>Douglas Co Surveyors Office - Larry E Monrean, Deputy - Karen Cheney; Peter Earle - Jan. 13, 1977 - C.S. File 59/29-11</p> <p>-----</p> <p>Found - 1¼" I.P. approx. 14" above ground. A D.Fir 8" now 27" bears N.20½°E., 19.8 ft. Blaze has been previously partially opened, is now well healed. A R.Fir 16" now 22" bears S.2°W., 13.0 ft. Tree has pitched over blaze. SE BT, per Cain, is now down. Lying ENE of record position approx. 10 ft. Set 1" x 30" I.P. with brass cap attached at ¼ cor. stamped: Douglas County Surveyor T 29 S R 7 W ¼ S 8 S 17 1977</p> <p>Set 1¼" x 36" I.P. beside cap.</p>
<p>Found OK by DeGroot, June 1997 - M 124-57</p>
<p>Fd. Ok by BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1745, surveyed Aug. 1994 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20077-8)</p>