

PRIMARY CORNER DESCRIPTION 1/4 Cor. For Secs. 5 and 8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6546)

-----  
Set 1/4 sec. post, at average distance, from which  
A B.Oak 20" dia., bears N.35°W., 15 lks. dist.  
A B.Oak 9" dia., bears S.77½°E., 12 lks. dist.

James Artman Surveying - For: Keller Lumber and Clarence Beeman - Dec. 1990 - M 111-17

-----  
Found - 22" B.Oak bears S.77½°E., 7.9 ft. reverse scribes "1/4 S" on back of chopped and rotted face (orig. BT)  
Set 5/8" x 30" Iron rod with 1" cap mkd: Artman RLS 2268.  
New BTs -7" Cedar bears N.18°E., 17.2 ft. scribed 1/4 S5 BT.  
5" Cedar bears S.19°E., 21.1 ft. scribed 1/4 S8 BT.  
10" D.Fir bears S.6°W., 24.6 ft. scribed 1/4 S8 BT.  
7" Pine bears N.89°W., 36.6 ft. scribed 1/4 S5 BT.  
Corner falls 15 ft. South of an E-W fence line.

Neil Hibbs - For: Roland Theiss - 1/2013 - M157-69

-----  
This corner set per orig. BT per M111-17. RM 2-46 incorrectly computed this corner at proportioned position between points B and C, (Section corners on the map).  
Found rod bears S.61°54'59"E., 80.99 ft. from mid-point between B and C, (Section corners on the map) as computed per RM 2-46