

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION So. Sec. Cor., 32 & 33 Only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6521)

-----  
Set a post, at proper dist., cor. of secs. 4 & 5, 32 & 33, from which;

- A Laurel, 10" dia., bears N.53°W., 41 lks.
- A Laurel, 4" dia., bears N.35°E., 72 lks.
- A Laurel, 5" dia., bears S.53°E., 100 lks.
- A B. Oak, 6" dia., bears S.27°W., 82 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6040)

-----  
Set an iron post, 3' long, 2" dia., 28" in the ground, for cor. of secs. 32 & 33, with brass cap mkd:

|      |      |
|------|------|
| T29S | R7W  |
| S 32 | S 33 |
| 1924 |      |

from which

- A Laurel, 12" dia., bears N.36°E., 43 lks., mkd: T29S R7W S33 BT.
- A Fir, 14" dia., bears N.72°W., 16 lks., mkd: T29S T7W S32 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell & Dale McFarland - June 1962 - C.S. 49/139-79

-----  
Found - Brass cap set in 1924

Fir stump bearing N.72°W., 10.6'  
Cat road where Laurel BT would have been.

New BTs- 13" Fir, N.34½°E., 57.4' scribed T29S R7W S33 CSBT  
15" Fir, N.28°W., 88.8' scribed T29S R7W S32 CS BT.

Fd. 1924 brass cap and 3 BTs. BLM survey by Wofford, Popken and Carlson, Surveyed, 1974-76 (DCSO records, Vol. 39 Page 15817)

FD OK By - BLM resurvey, by Boyd W. Peterson, under special instructions dated August 8, 1988. Surveyed Sept./Dec. 1988 (DCSO records Vol. 49 Pages 18814 & 18815)

Found OK by T. Baker, Oct. 2000 - M136-9 A&B