

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6534)

Set ¼ sec. post.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5961)

Intersect the point for ¼ sec.cor., as restored by County Surveyor at cor. of fence, bears S. and W. Ford's notes do not describe any bearing trees at this cor., but a laurel, 36" dia., bears N.14°E., 28 lks. dist., marks are plain and indicate they were made by Ford, and an Oak, rotted down, bears S.70°W., 20 lks. dist., marks show on the log.

At the fence cor.

Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked:

¼
S32 | S33
1924

from which

A Fir 6" dia., bears N.32°E., 15 lks. mkd. ¼ S33
BT.

A Fir 7" dia., bears N.27°W., 23 lks. mkd. ¼ S32 BT.

(Note: Found no record of a County visit prior to this 1924 Mensch survey. Could have possibly been Stewart in 1923. See C.S. File 17/39)

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - May 1962 - C.S. File 49/139-61

Found - Brass cap at cor. and NE BT. NW BT not found.
New BT - 13" R.Fir bears N.80°W., 9.0 ft. scribed ¼ S32 CSBT

Brass cap and 4 BTs, Fd. OK, BLM survey by Jelley and Rogers, 1981 - (DCSO records, Vol. 43 Page 16695)

Found OK by T. Baker, Oct. 2000 - M136-9 A&B