

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec Cor for 28, 29, 32 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6534)

-----  
Set a post cor. of secs. 28, 29, 32 and 33, from which  
A W.Oak 12" dia., bears S.55°E., 119 lks. dist.  
A W.Oak 18" dia., bears N.30°E., 152 lks. dist.  
A B.Oak 18" dia., bears N.71½°W., 143 lks. dist.  
A W.Oak 9" dia., bears S.83°W., 100 lks. dist.

(Found no record source or date for this recorded renewal - Ren. #51 in old records)

-----  
Set Post. Set cor. from stump and O.B.T.  
W.Oak 12" S.55°E., 119 lks. O.B.T.  
W.Oak 5" S.62½°W., 11 lks. N.B.T.  
W.Oak 6" N.84½°W., 63 lks. N.B.T.  
W.Oak 5" N.66°E., 40 lks. N.B.T.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5960-61)

-----  
Intersect the point for cor. of secs. 28, 29, 32 and 33, located by record bearing and distance from the original SE bearing tree on which the marks are plain.

At the exact cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor., with brass cap mkd:

T29S	R7W
S29	S28
S32	S33
1924	

from which, the original bearing trees

A B.Oak 30" dia., bears S.55°E., 119 lks. marks legible.

Stump holes of NW and SW bearing trees further evidence the position of the old cor.

New Bearing trees

A W.Oak 6" dia., bears N.36½°E., 42 lks. dist., mkd. T29S R7W S28 BT.

A B.Oak 10" dia., bears S.51°E., 52 lks. mkd. T29S R7W S33 BT.

A W.Oak 10" dia., bears S.62½°W., 11 lks. dist., mkd. T29S R7W S32 BT.

A W.Oak 12" dia., bears N.84½°W., 63 lks. dist., mkd. T29S R7W S29 BT.

Douglas Co. Surveyors Office - Ben B. Irving; James Byron; Ray Irving - Work done for County Engineer, Rd. #38 - Feb. 1954 - C.S. File 46/36

----- (Cont. Next Page)

