TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6536)

Set ¼ sec. post, from which
A Laurel 8" dia., bears S.10°E., 85 lks. dist.
A Red Fir 10" dia., bears N.20°E., 68 lks. dist.

BLM survey by John M. Jelley, under Contract #346, Surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14296-97)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap marked: T 29 S R 7 W

¼
S 20 | S 21
1966

from which
A Fir 13" dia., bears S.65°E., 146 lks. mkd. ¼ S21 BT.
A Fir 13" dia., bears N.76°W., 43 lks. mkd. ¼ S20 BT.
Set a steel fence post, 6 ft. long, alongside the iron post.
From this point, an iron rod, ½" dia., firmly set, extending 6" above ground, bears S.52°W., 0.73 chs. dist.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - A. Victor Cangie; Mike Tompkins - Jan. 10, 1977 - C.S. File 59/29-5

Found - 1966 BLM brass cap on 2½" I.P. set flush in the ground near the bottom of the cutbank, approx. 10 ft. west of the west edge of the asphalt concrete of Olalla Road, cap properly marked.
This cap is oriented facing South with steel fence post alongside. From which
A 13" now 14" D.Fir alive and well healed, bears S.65°E., 96.4 ft.
A 13" now 13" D.Fir snag, burned and well healed bears N.76°W., 28.4 ft.
New BT - 13" D.Fir bears N.50½°E., 192.3 ft. scribed "¼ S21 CS BT" on a double blaze.

Fd. OK, by M. Heimburger, Land Partition 1992-0035