

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6537)

-
- Set post corner of secs. 8, 9, 16 and 17, from which
- A W.Oak 78" dia., bears S.34°E., 247 lks. dist.
 - A B.Oak 18" dia., bears N.20°E., 105 lks. dist.
 - A B.Oak 16" dia., bears N.14°W., 117 lks. dist.
 - A B.Oak 12" dia., bears S.50°W., 128 lks. dist.

Douglas Co. Surveyors Office - Frank Cain, May 11, 1913 - Field Book 63 Pgs. 52-56; C.S. File 6/26

-
- Set post 3" x 3" x 36", 16" in the ground.
- A B.Oak 36" dia., N.79°30'E., 368 lks.
 - A W.Oak 20" dia., S.12°15'E., 262 lks.
 - A B.Oak 30" dia., N.89°15'W., 232 lks.
 - A B.Oak 20" dia., S.70°45'W., 249 lks.

Frank Richardson; E.S. Woodford - May 1945 (No record source found. (Old Co. Ren. #46)

-
- Renewed from old bearing trees. Marked
- A 24" Cedar S.38°15'W., 133.6 ft.
 - A 24" Fir N.50°45'W., 89.6 ft.
 - A 20" W.Oak S.12¼°E., 172.9 ft. Old BT, in good condition.

Douglas Co. Surveyors Office - Ben B. Irving; James W. Byron, Ray Irving - Work done for County Engineer, Rd. #38 - Feb. 1954 - C.S. File 46/36

-
- Corner renewed from 24" Cedar, S.38¼°W., 133.6 ft., in good condition. 20" W.Oak S.12¼°E., 172.9 ft. in fair condition. Found a yellow tag on fence corner at corner. Set a 36" x 1" I.P. with brass cap mkd. Sec. 8, Sec. 9, Sec. 16, Sec. 17, County Surveyor's office T29S R7W 1954. Blazed and scribed two trees:
- Red Fir 14" dia., N.2°15'E., 90.4 ft. mkd. S8 CS BT.
 - Red Fir 12" dia., S.40°E., 125.3 ft. mkd. S16 CS BT.

GLO resurvey by Hans W. Thielsen, under Group #316, Surveyed, July/Aug. 1955 - (DCSO records Vol. 28 Page(s) 11770-71)

-
- The Sec. cor., perpetuated with an iron post, 1" dia., 8" above ground, with brass cap mkd: COUNTY SURVEYOR S 8 S 9 S 17 S 16 1954. All bearing trees have been destroyed by logging operations. At the cor. point

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Set an iron post, 3 ft. long, 2" dia., 28" in the ground,
with brass cap mkd:

T 29 S R 7 W
S 8 S 9
S 17 S 16
1955

from which

A Walnut 6" dia., bears N.52¼°E., 118 lks. dist., mkd.
T29S R7W S9 BT.

A B.Oak 30" dia., bears S.16½°E., 264 lks. dist., mkd.
T29S R7W S16 BT.

A W.Oak 8" dia., bears S.39°W., 153 lks. dist., mkd. T29S
R7W S17 BT.

A Madrona 9" dia., bears N.28°W., 105 lks. dist., mkd.
T29S R7W S8 BT.

Reset the 1" post alongside the 2" post.

Fd. OK, Feb. 1993, Donald Bentz, M 116-49