

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. 4 & 5; 32 & 33 of T28-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5749)

Set a post at proper distance, cor. of secs. 4, 5, 32 and 33, made a trench and drove a charred stake, 12" long, as per instructions.

Glenn Baughman, LS #536 - for: Paul Slama - May 1973 RM 2-46; C.S. File 55/296

Set Brass cap by proportion, mkd: T28S R7W
S 32 | S 33
S 5 | S 4
T29S R7W
OLS 536 1973

Bearing Objects: 2'x3'x2½' S.70°W 92.4 ft.
Chiseled 6" X in ~~10'x15'x5'~~ rock bears ~~N.18¼°W., 56.34 ft.~~
4'x6'x2' N87°E.,
Chiseled 6" X in ~~2'x6'x1'~~, north face rock, bears ~~S.23½°W.,~~
86.0 ft.
~~19.25 ft.~~ 2'x3'x1½' S.44°E., 87.3 ft.
Chiseled 6" X in ~~3'x5'x1½'~~ rock bears ~~S.34°E., 117.8 ft.~~
(Corrections made and recorded in C.S. File 55/296)

FD. BC G. Lang 10/10, M161-28