

PRIMARY CORNER DESCRIPTION Center West 1/16 Cor. Sec. 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM survey by John M. Jelley, under Group #346, Surveyed, Aug/Oct. 1966 (DCSO records Vol. 34 Page(s) 14301)

-----  
Set an Iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

C — W 1/16 — C  
          S 21  
          1966

from which

A Fir 8" dia., bears N.13°E., 17½ lks. dist., mkd. CW 1/16 S21 BT.

An Oak 18" dia., bears S.11°E., 41½ lks. dist., mkd. CW 1/16 S21 BT.

Douglas Co. Surveyors Office - L.E. Monrean; P. Earle; J.H.C. Nov. 3, 1975 - C.S. File 57/39-2

-----  
Found - BLM Cadastral brass cap properly marked. (1966)  
A Fir snag, 8" now 9" dia., bears N.15°E., 11.6 ft. (Rec. N.13°E.) scribed "CW 1/16 S21 BT".  
An Oak stump 18" dia., bears S.8°E., 26.2 ft. (Rec. S.11°E., 27.4 ft.) scribed "CW 1/16 S21", stump cut flush with ground, portion of scribed tree setting on top. Stump enclosed in Galv. metal cylinder, on edge of logging road.

New bearing objects:

Set 5/8" dia. Iron rod in a 46" dia. Fir stump. Placed Co. Surveyors Office alum. cap on rod and stamped "B.O.#1" bears S.14°W., 16.9 ft.

Set 5/8" dia. Iron rod in 28" dia. Fir stump. Placed Co. Surveyors Office alum. cap on rod and stamped "BO #2", bears N.60½°E., 41.0 ft.

A D.Fir 29" dia., bears N.54½°E., 113.0 ft. Tree blazed and scribed "CW 1/16 S21 CS BT".