

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 320551

PRIMARY CORNER DESCRIPTION CC of N-S c/line, NW¼ S. 9 w/DLC40

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Hans Theilson, under group #316 - Surveyed, July/Aug. 1955 (DCSO records Vol. 28 Page(s) 11779-80)

Intersect S. bdy. of donation land claim No. 40.
At the intersection point
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd:

C 40

W
5
CC | S 9

W
1955

from which
A Fir 25" dia., bears S.67°E., 31 lks. dist., mkd. WW S9
CC BT.
A Fir 21" dia., bears S.21°W., 48 lks. dist., mkd. L 5 WW
S9 CC BT.

From this corner the point for the southeast corner of donation land claim No. 40 bears S.86°41'E., 3.34 chs. dist.

From the same corner the point for the southwest corner of donation land claim No. 40 bears N.86°41'W., 46.66 chs. dist.

Douglas Co. Surveyors Office - John M. Powell; W. Penley; J. Heritage - Oct. 19, 1970 - C.S. File 49/139-131

Found - 1955 GLO brass cap at closing corner, properly marked.
25" D.Fir, now stump, S.67°E., 20.5 ft. scribe visible W W S9 CC BT.
21" D.Fir now 36" S.21°W., 31.7 ft. shows good scar.
New BT - 14" D.Fir S.73°E., 21.0 ft. scribed "CC S9 CS BT"

BLM resurvey by Berry & Popken, under Group #316 - Surveyed, April 1973 - (DCSO records Vol. 39 Page(s) 15808-09)

Intersect the S. bdy. of Donation Land Claim No. 40, and point for the closing cor. on the N. and S. center line of the NW ¼ of sec.9.
From this point the closing cor. on the N. and S. center line of the NW¼ of sec. 9, erroneously established by Thielsen, in 1955, bears S.0°35'E., 0.398 chs. dist., set and marked and witnessed as described in the official record. I remove the iron post, destroy the marks on the bearing trees, and at the point of intersection
(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 320551

PRIMARY CORNER DESCRIPTION CC of N-S C/L of NW¼ S9 W/DIC 40

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Reset the iron post, 36" long, 1" dia., 30" in the ground,
with brass cap mkd.

C 40
W

5
CC | S 9
W
1955

from which

A Fir 6" dia., bears S.36°E., 32 lks. dist., mkd. WW S9 CC
BT.

A Fir 33" dia., bears S.12°W., 88 lks. dist., mkd. L5 WW
S9 CC BT.

Add marks 1973 to brass cap.