

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 33 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6521)

Set ¼ sec. post, at proper dist., from which,
A Laurel, 15" dia., bears S.10°W., 30 lks.
A Laurel, 8" dia., bears N.17°W., 50 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6041)

Intersect the point for ¼ sec. cor., located by measurement from the orig. bearing trees.

At the exact corner point

Set an iron post, 3' long, 1" diam., 28" in the ground, for ¼ sec. cor. of sec. 33 only, with brass cap mkd:

¼ S33
1924

from which (the Orig. BTs)

A Laurel, 22" dia., bears N.17°W., 50 lks., marks rotted away.

A Laurel, 24" dia., bears S.10°W., 30 lks., blazes show plainly, but marks have been obliterated.

New bearing trees:

A Fir, 10" dia., bears N.43°E., 23 lks., mkd: ¼ S 33 BT

A Fir, 7" dia., bears N.49°W., 18 lks., mkd: ¼ S 33 BT

BLM resurvey by Harvey Wofford, G. Steven Popken, & James J. Carlson, instructions dated August 29, 1974 under Group #851. Surveyed Sept. 1974/May 1976 (DCSO records Vol. 39 Pages 15816)

The ¼ sec. cor. of sec. 33 only, on the S. bdy. of T29S R7W, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap mkd: ¼ S33

1924

from which the remains of the original bearing trees

A root hole, bears S.10°W., 30 lks., with a down and decayed madrone alongside, 24" dia., no marks visible.

A decayed madrone stump, 18" dia., bears N.17°W., 50 lks., no marks visible.

and bearing trees mkd. by Mensch

A Fir, 15" dia., bears N.43°E., 23 lks., with healed double blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir, 10" dia., bears N.46°W., 18 lks., with healed double blaze. (Record, N.49°W.)

Fd. OK, 1924 brass cap and 4 BTs. BLM survey by Jelley and Rogers, 1981 (DCSO record, Vol. 43 Pages 16692-93)