

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6535)

Set ¼ sec. post, average distance, from which
A B.Oak 16" dia., bears S.84°W., 36 lks.
A Pine, 36" dia., bears N.61°E., 14 lks.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5962-63)

Intersect the point for ¼ sec. cor. located by measurement from the original bearing trees, both of which are down, but blazes show on SW tree.

At the exact cor. point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec.cor. with brass cap marked:

¼ $\frac{S29}{S33}$
1924

from which, the original bearing trees:

An Oak stump hole bears S.84°W., 36 lks. dist.

A Pine stump hole, bears N.61°E., 14 lks. dist.

New Bearing trees:

A Fir 12" dia., bears S.50°E., 11 lks. mkd. ¼ S3 BT.

A Fir 16" dia., bears N.60°W., 9 lks. mkd. ¼ S28 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell and Dale McFarland - May 1962 - C.S. File 49/139-60

Found - GLO brass cap at corner. Both BTs, now stumps. SE BT shows good scribing "BT".

New BTs -9" Cedar N.44°E., 65.0 ft. scribed ¼ S28 CS BT.

11" R.Fir S.76°W., 67.4 ft. scribed ¼ S33 CS BT.

Fence corner runs East, West and South from corner.

BLM survey by Jelley and Rogers, under Group #1044, Surveyed, Jan./April 1981 - (DCSO records Vol. 43 Page(s) 16680-81)

The ¼ sec. cor. of secs. 28 and 33, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap mkd. ¼ $\frac{S28}{S33}$

1924

from which the remains of bearing trees mkd. by Mensch

A burned Fir stump 17" dia., bears N.60°W., 9 lks. dist., with fragmentary scribe marks visible on open blaze.

A burned Fir stump 13" dia., bears S.50°E., 11 lks. dist., with scribe marks BT visible on open and burned blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees:
A Fir 10" dia., bears N. 10 3/4°E., 87 lks. dist., mkd.
1/4 S28 BT.
A Madrone, 6" dia., bears S. 4 1/4°E., 63 1/2 lks. dist., mkd. 1/4
S33 BT on bark.