

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 21 and 28

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Set ¼ sec. post, at average distance, from which
A B.Oak 8" dia., bears S.64°E., 62 lks. dist.
A B.Oak 24" dia., bears N.72°W., 94 lks. dist.

BLM survey by John M. Jelley under Contract #346, Surveyed,
Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14295)

The ¼ sec. cor. determined at record bearing and distance
from the original bearing trees:

An Oak root crown, size indeterminate, bears N.72°W., 94
lks. dist., no marks remaining.

A down Oak 14" dia., bears S.64°E., 62 lks. dist, with
scribe marks ¼ S BT visible in negative on rotted
overgrowth.

At the cor. point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd: T 29 S R 7 W

¼ S 21
S 28
1966

from which new bearing trees:

A W.Fir 21" dia., bears N.58°E., 86 lks. dist., mkd. ¼ S21
BT.

A Fir 8" dia., bears S.60°E., 43 lks. mkd. ¼ S28 BT.