

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

| Alias | Description |
|-------|-------------|
| _____ | _____       |
| Alias | Description |
| _____ | _____       |
| Alias | Description |
| _____ | _____       |
| Alias | Description |
| _____ | _____       |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6537)

-----  
Set ¼ sec. post, at average distance.  
Made a mound of stone on top of stony point, no timber in a reasonable distance.

BLM resurvey by John M. Jelley, under Group #346, Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14298)

-----  
Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an Iron post 28" long, 2½" dia., 23" in the ground, with brass cap mkd:

T 29 S R 7 W

¼  $\frac{S\ 16}{S\ 21}$

1966

from which

A Fir 30" dia., bears N.30½°E., 77 lks., mkd. ¼ S16 BT.

A Fir 28" dia., bears S.84°W., 14 lks., mkd. ¼ S21 BT.

Fd ok, Set 6' steel post 2 ft. S.88°E. by D. Edwards - 4/2014  
- M167-73