

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6538)

-----  
Set 1/4 sec. post, at average distance, from which  
A B.Oak 10" dia., bears N.3°W., 34 lks.  
A B.Oak 8" dia., bears S.45°W., 19 lks.

GLO resurvey by Hans W. Thielsen under Group #316, Surveyed, July/Aug. 1955 - (DCSO records Vol. 28 Page(s) 11770)

-----  
Point for the 1/4 sec. cor. of secs.9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

1/4  $\frac{S\ 9}{S\ 16}$   
1955

from which

A Fir 18" dia., bears N.30°W., 25 lks., mkd. 1/4 S9 BT.  
A Fir 10" dia., bears S.74°W., 24 lks., marked 1/4 S16 BT.

Fd ok, by D. Edwards - 4/2014 - M167-73