

PRIMARY CORNER DESCRIPTION Center ¼ Cor. for Sec. 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Hans W. Thielsen, under Group #316, Surveyed, July/Aug. 1955 - (DCSO records Vol. 28 Page(s) 11775)

-----  
Point for the center ¼ sec. cor. of sec.9, at intersection with E. and W. center line.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

C ¼ S 9  
1955

from which

A Fir 15" dia., bears N.86¼°E., 91 lks. dist., marked C ¼ S 9 BT.

A W.Oak 8" dia., bears N.59½°W., 36 lks. dist., marked C ¼ S 9 BT.

-----  
David Edwards - For: Roseburg Resources - 1/2008 - M 155-3

Found - BLM Brass cap

New BTs- 8" Fir N.5°E., 25.7'

12" Fir S.79°W., 9.46'

-----  
David Edwards, LS 2339 - Brant Miller - 10/10/2012 - C.S. File 65/77/44

Found - 1955 GLO brass cap/iron pipe in good condition.  
12" dia. Fir, 5.5' tall stump bears N.79°E. (S.79°W.) 9.5' (scribe visible) 2008  
9" dia. Fir, 48" tall stump bears S.5°W., (N.5°E.) 25.' (scribed visible) 2008

New - Set three 6"x30" steel rebars with red plastic caps mkd: "D.A. EDWARDS LS 2339" as follows:

N.43°E., 25.0'

S.43°W., 25.0'

N.20°W., 11.15'

A 6 ft. steel post is set East 1.5'