

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6539)

Set ¼ sec. post, at average distance, from which
A B.Oak 16" dia., bears S.62°W., 212 lks. dist.
A W.oak 10" dia., bears N.83½°W., 213 lks. dist.

Oscar F.Thiel, Co. Surveyor - For: F.T. Fisher & Casterline
April 1899 - Vol. 2 Pg. 261 and Vol. 2 Pg. 77

Set a sandstone 12 x 10 x 10 ins. from which a W.Oak 7" dia., bears S.4°W., 2.50 chs. distant.
A W.Oak 34" dia., bears N.73°W., 2.44 chs. dist.
One original BT standing but dead and stump of the other remaining; part of letters visible.

GLO resurvey by Hans W. Thielsen, under Group #316, Surveyed July/Aug. 1955 - (DCSO records Vol. 28 Page(s) 11774)

The ¼ sec. cor., determined at record bearing and distance from a bearing tree marked by the County Surveyor in 1890
A W.Oak 36" dia., bears N.73°W., 244 lks. dist., with marks BT uncovered.
At the Corner point
Set an Iron post, 3 ft. long, 1" dia., 35" in the ground, with brass cap mkd: ¼ $\frac{S\ 4}{S\ 9}$
1955
from which new bearing trees:
A W.oak 8" dia., bears N.44°E., 352 lks., mkd. ¼ S4 BT.
A W.Oak 14" dia., bears S.11°W., 227 lks. mkd. ¼ S9 BT.

Fd. 1955 brass cap and 3 references, BLM survey by Berry and Popken, 973 (DCSO records, Vol. 39 Page 15806)

FD. Ok by D. Edwards, 1/2008 - M155-3