

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 4; & 33 of T28-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5749)

-----  
Set ¼ sec. post, at proper distance, from which  
A B.Oak 6" dia., bears S.25°E., 161 lks. dist.  
A W.Oak 40" dia., bears N.2°W., 425 lks. dist.

Doug. County Surveyors Office - Karen Reed; Terrie Plouff  
Aug. 24, 1982 - C.S. File 62/1-14

-----  
Found - No original post found.  
A 6" x 12" quartz rock (origin unknown) now 13" x 8" x 6" quartz rock as used in 1957 survey by A. Boyer, M 12-72 and 1973 survey by G. Baughman, RM 2-46, DCSO records. No marks on stone.  
A 40" dia., B.Oak with previously cut out blaze, rotted center bears S.25°E., 106.3 ft. (Rec.)  
This tree was referred to as the orig. 6" B.Oak in the above mentioned surveys. No visible scribe found.

Set 1" x 30" Iron pipe with brass cap stamped "Douglas County Surveyor T28S 1/4 S33 R7W S4 T29S 1982", at record bearing & distance from 40" Oak, which is the position of found stone, protruding 10" above the ground with quartz rock along south side of cap. Set this corner to perpetuate a used corner position.

New Accessories:

- 13" dia. B.Oak scribed "1/4 S4 CS BT" in a double blaze bears S.11 3/4°W., 128.1 ft. dist.
- 5/8" x 30" Iron rod with alum. cap stamped "BO 1" and Douglas Co. Surveyor" bears N.43°W., 32.95 ft. Set flush with ground.
- 5/8" x 30" Iron rod with alum. cap stamped "BO 2" and "Douglas Co Surveyor", bears N.62°E., 35.60 ft. Set flush with ground.

No other trees within reasonable range.  
Corner falls on a west slope 0.9 ft. West of a N-S fence.