

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 33 & 34 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6521)

-----  
Set a post, at proper distance, cor. of sec. 3, 4, 33 & 34, from which:

- A Laurel, 20" dia., bears N.65°E., 55 lks.
- A B.Oak, 7" dia., bears N.65°W., 29 lks.
- A B.Oak, 8" dia., bears S.63°E., 138 lks.
- A B.Oak, 8" dia., bears S.53°W., 44 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6042)

-----  
Intersect the point for cor. of secs. 3, 4, 33, & 34, located by measurement for the orig. bearing trees.

At the exact cor. point

Set an iron post, 3" long, 2" dia., 28" in the ground, for cor. of secs. 33 & 34, with brass cap mkd:

T29S R7W  
S33 S34  
1924

from which (the orig. bearing trees)

- A Laurel, 40" dia., bears N.55°E., 55 lks., (not N.65°E.), marks are obliterated.
- Stump hole of a Black Oak, bears S.66°E., 128 lks. (not S.63°E. 138 lks.)
- A Black Oak snag, 12" dia., bears N.71°W., 29 lks. (not N.65°W.)
- A Black Oak, 14" dia., bears S.48°W., 44 lks. (not S.53°W.), marks visible.

New bearing trees:

- A Pine, 8" dia., bears N.80°E., 93 lks., mkd: T29S R7W S34 BT.
- A Fir, 10" dia., bears N.60°W., 93 lks., mkd: T29S R7W S33 BT.

BLM resurvey by Harvey Wofford, G. Steven Popken, & James J. Carlson, instructions dated August 29, 1974 under Group #851. Surveyed Sept. 1974/May 1976 (DCSO records Vol. 39 Pages 15814-15)

-----  
The cor. of secs. 33 & 34 only, on the S. bdy. of the Tp. monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with brass cap mkd:

T29S R7W  
S33 S34

(Cont. Next Page)

1924

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 33 & 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the orig. bearing trees  
A Madrone, 38" dia., bears N.55°E., 55 lks., no marks visible on decayed blaze.  
A root hole, bears S.66°E., 128 lks.  
A root hole, bears S.48°W., 44 lks., with a down Black Oak alongside, 16" dia., no marks visible.  
and bearing trees marked by Mensch  
A Pine, 17" dia., bears N.80°E., 93 lks., with healed double blaze.  
A Fir, 17" dia., bears N.60°W., 93 lks., with healed double blaze.