

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6530)

Set 1/4 sec. post, from which
A B.Oak 8" dia., bears N.77°E., 22 lks.
A B.Oak 9" dia., bears S.70°W., 19 lks.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5964)

Intersect the point for 1/4 sec. cor., located by record bearing and distance from the original NE bearing tree.
At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor. with brass cap mkd
S33 | S34
1924

from which the original bearing trees:
A B.Oak 12" dia., bears N.77°E., 22 lks. dist., marks are legible.
An Oak stump bears S.70°W., 19 lks. dist.
New Bearing trees:
A Fir 6" dia., bears N.15 1/2°E., 22 lks. mkd. 1/4 S34 BT.
A Fir 26" dia., bears N.81°W., 54 lks. mkd. 1/4 S33 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - April/May 1962 - C.S. File 49/139-59

Found - Brass cap at corner. 1923 NW BT partly rotted, face burned. We do not find 1923 NE BT. Original NE BT shows old scars, center rotted.
New BTs -9" R.Fir bears S.45°E., 11.3 ft. scribed 1/4 S34 CSBT
8" R.Fir bears S.56°W., 10.2 ft. scribed 1/4 S33 CSBT

BLM survey by Jelley and Rogers, 1981, Fd. BC, one Mensch BT and Byron's trees. (DCSO records, Vol. 43 Pgs. 16693-94)