

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6530)

Set a post, cor. of secs. 27, 28, 33 and 34, from which
A Laurel 10" dia., bears S.46°E., 23 lks. dist.
A Laurel 16" dia., bears N.47°E., 36 lks. dist.
A B.Oak 8" dia., bears N.37½°W., 13 lks. dist.
A Laurel 14" dia., bears S.78°W., 50 lks. dist.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5963)

Intersect the point for cor. of secs. 27, 28, 33 and 34, located by measurement from the original bearing trees.
At the exact cor. point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for sec. cor., with brass cap marked:

T29S	R7W
S28	S27
S33	S34
1924	

from which the original bearing trees:
A Laurel 30" dia., bears N.32°E., 36 lks. (not N.47°E.)
A Laurel 24" dia., bears S.46°E., 23 lks. remarked T29S R7W S34 BT.
A Laurel 22" dia., bears S.80°W., 50 lks. (not S.78°W.) remarked T29S R7W S33 BT.
An Oak stump bears N.47°W., 23 lks. (not N.37°W 13 lks.), blazes are plain on the stump.
New Bearing trees:
A Fir 6" dia, bears N.24°E., 14 lks marked T29S R7W S27 BT
A Cedar 14" dia., bears N.70°W., 41 lks. dist. marked T29S R7W S28 BT.

GL0 resurvey by Hans W. Thielsen under Group #346, Surveyed, April/May 1957 (DCSO records Vol. 28 Page(s) 12155-56)

The Sec. cor. determined from each of the original bearing trees and trees mkd. by Mensch in 1924. The iron post set by Mensch is gone.
At the corner point
Set an Iron post, 3 ft. long, 2" dia., 28" in the ground with brass cap marked:

T29S	R7W
S 28	S27
S 33	S34
1957	

from which the original bearing trees:
A Madrona 30" dia., bears N.32°E., 36 lks. dist., with partial scribe marks visible. (Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. cor. for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Madrona 24" dia., bears S.46°E., 23 lks. dist., marked T29S R7W S34 BT on unhealed blaze.
A Madrona 22" dia., bears S.80°W., 50 lks. dist., marked T29S R7W S33 BT on unhealed blaze.
A rotted Oak stump, size indeterminate, bears N.47°W., 23 lks. dist., with no marks remaining.
and trees marked by Mensch in 1924:
A Fir 30" dia., bears N.24°E., 14 lks. dist., plainly blazed and healed.
A Cedar 20" dia., bears N.70°W., 41 lks. dist., with partial scribe marks visible on unhealed blaze.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell; Dale McFarland - May 1962 - C.S. File 49/139-60

Found - GLO brass cap at corner. NE and NW BTs OK, recorded in 1924 survey.
I rescribe, now 24" Laurel S.80°W., 33.0 ft. "S33 T29S R7W CS BT".
I rescribe, now 26" Laurel S.46°E., 15.2 ft. "S34 T29S R7W CS BT".

Corner Fd. OK, BLM resurvey by Wofford, Popken and Carlson, 1974-76. (DCSO records, Vol. 39 Pgs. 15820-21)

BLM resurvey by Jelley and Rogers, under Group #1044. Surveyed Jan/April 1981 (DCSO records Vol. 43 Pages 16679-80)

Found corner monumented with 1957 brass cap.
from which the remaining original bearing trees:
A Madrone 30" dia., bears S.46°E., 23 lks. dist., with scribe marks 9S R7W S34 CS BT visible on open blaze.
This tree was rescribed by Byron in 1962.
A Madrone 28" dia., bears S.80°W., 48 lks. dist., with scribe marks 29S R7W S33 CS BT visible on open blaze.
This tree was rescribed by Byron in 1962.
and the remains of bearing trees by Mensch:
A Fir snag 12" dia., bears N.29°E., 14 lks. dist., with healed blaze. (Rec. N.24°E.)
A Cedar 20" dia., bears N.70°W., 41 lks. dist., with healed blaze. (Rec. N.68¼°W.)
and a new bearing tree:
A Fir 8" dia., N.41°E., 40 lks. mkd. T29S R7W S27 BT.

Fd. BC & BTs of record, 10/2017 - by N Hibbs, C.S. 65/97-3