

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400214

PRIMARY CORNER DESCRIPTION Bell Placer Mine Cor. No. 1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

MS Bell Placer Mine, by Commissioners Letter "N" dated Nov. 23, 1897 and made under instructions of the Surveyor General for Oregon, dated Dec. 10, 1897. Surveyed Dec 1897 - (DCSO records Vol. 56 Page(s) 22259)

On the West line of Sec. 27 T29S., R7W., from which the South West corner of Sec. 27 bears S.0°55'W. ~~930 ft.~~ 14.09 chs
A fir post 4 ft. long 4 ins square set 2 ft in the ground with mound of earth and stone, scribed S.M.S. 1, whence
A red fir 16 ins. diam. bears N.82°45'E., 10 ft and
A white fir 8 ins. diam. bears S.37°57'W., 27.2 ft.
Each blazed and scribed S.M.S-1 BT.

BLM resurvey by Wofford, Popken and Carlson, under Group #851. Surveyed, Sept. 1974/May 1976 (DCSO records Vol. 39 Page(s) 15821)

Intersect Cor. No. 1 of Bell Placer Mine, determined at record hearing and distance from the remains of the original bearing trees:
A sawed fir stump, 26" dia., bears N.82¾°E., 15 lks., with scribe marks BT visible on opened blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.
T29S | BP
R 7W | 1
S 28 | S 27
1974
from which
A W.Fir, 17" dia., bears N.74½°E., 41 lks., mkd: BP 1 BT.
A W.Fir, 9" dia., bears S.74°W., 14 lks., mkd: BP 1 BT.