

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400223

PRIMARY CORNER DESCRIPTION Bell Placer Mine Cor. No. 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

MS Bell Placer Mine, by Commissioners Letter "N" dated Nov. 23, 1897 and made under instructions of the Surveyor General for Oregon, dated Dec. 10, 1897. Surveyed Dec 1897 - (DCSO records Vol. 56 Page(s) 22259-60)

A fir post 4 ft long 4 ins long 4 ins square set 2 ft in the ground with mound of earth, scribed S.M.S. 2, whence
A black oak 10 ins. diam. bears S.28°15'E., 9.3 ft. and
A red fir 6 ins. diam. bears N.70°W., 2.9 ft.
Each blazed and scribed S.M.S. 2 BT.
The ¼ sec. cor. on west line of sec. 27 bears N.0°55'E., ~~1185.6 ft.~~ 16.82 chs.

BLM resurvey by Wofford, Popken and Carlson, under Group #851. Surveyed, Sept. 1974/May 1976 (DCSO records Vol. 39 Page(s) 15821-2)

Point for Cor. No. 2 of Bell Placer Mine, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.
T29S | BP
R 7W | S 27
S 28 | 2
1974

from which
A fir, 7" dia., bears S.48½°E., 53 lks., mkd. BP 2 BT.
A fir, 10" dia., bears N.30½°W., 115 lks., mkd. BP 2 BT.