

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6530-31)

- 
- Set a post, cor. of secs. 21, 22, 27 and 28, from which
- A Laurel 18" dia., bears S.35½°E., 153 lks. dist.
  - A B.Oak 20" dia., bears N.38½°E., 50 lks. dist.
  - A Laurel 8" dia., bears N.32°W., 97 lks. dist.
  - A B.Oak 8" dia., bears S.52°W., 166 lks. dist.

BLM resurvey by John M. Jelley, under Group #346 - Surveyed, Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14290-91)

-----  
At the corner of secs. 21, 22, 27 and 28, determined at record bearing and distance from the remaining original bearing trees:

- A Madrone 35" dia., bears S.35½°E., 153 lks. dist., with scribe marks S27 BT visible on opened blaze.
- A rotted remains of an Oak, size indeterminate bears S.52°W., 166 lks. with scribe marks S BT visible in negative on section of overgrowth.

At the cor. point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 29	S R 7 W
<u>S 21</u>	<u>S 22</u>
S 28	S 27
1966	

from which new bearing trees

- A Fir 15" dia., bears N.80°E., 193 lks. dist., mkd. T29S R7W S22 BT.
- A Fir 10" dia., bears S.69°W., 94 lks. dist., mkd. T29S R7W S28 BT.
- A Fir 13" dia., bears N.18°W., 200 lks. dist., mkd. T29S R7W S21 BT.

Corner Fd. OK, BLM survey by Wofford, Popken and Carlson, 1976 (DCSO records, Vol. 39 Pages 15822-23)

Leonard Herzstein - Witness: Maggie Herzstein - May 13, 2008 & June 4, 2008 - C.S. File 65/63-21

-----  
Found - 2¼" outside dia. iron pipe, firmly set by Jelley in 1966, projecting 8" above the ground, with a 3¼" dia. brass cap attached (properly)marked.

From which the remaining orig BT Ford in 1855

- A 44" madrone, bears S.35°30' E., 101.0 ft (rec per 1855 & 1966) S.35½°E., 153 links = 100.98 ft), with axe marks visible on partially decayed opened blaze. continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

And from which the BTs marked by Jelley in 1966:  
A 22" D.Fir, bears S.69°00'W., 62.0 ft (rec per 1966 S.69°W. 94 lks = 62.04 ft) with healed blaze  
A 26" D.Fir, bears N.18°00'W., 132.0 ft, (rec per 1966, N.18°W. 200 lks = 132.00 ft) w/healed blaze  
NE bearing tree searched for and not found.

Description of Monuments and Accessories Established to Perpetuate the Corner: June 4, 2008

New BTs- A 13" D.Fir, bears N.12°05'E., 29.4 ft scribed "T29S R7W S22 BT" on a single blaze.

A 10" D.Fir, bears S.34°30'E., 12.0 ft, scribed "T29S R7W S27 BT" on a single blaze.

A 5 ft steel U-post, bears N.89°15'W., 1.4 ft driven 0.6 ft in the ground.

Note - Bearings are determined by a traverse to the East 1/16 corner of secs 21 & 28 and using the 1966 BLM rec. bearing on the sec line of N.89°15'W. The bearings are rounded to the nearest 05 minutes. New BTs have a 3/4" dia brass washer, stamped "LS 2150", nailed flush to the base of the blaze. Measurements are to the tree rootcrown Tree diameters are measured at breast height. The corner is approx 125 ft East of North-South rocky spur ridge and 80 feet West of a seasonal creek.