

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6531)

Set $\frac{1}{4}$ sec. post, from which
A B.Oak 9" dia., bears S.79°E., 17 lks.
A B.Oak 10" dia., bears N.20°W., 40 lks.

BLM resurvey by John M. Jelley, under Group #346, Surveyed, Aug./Oct. 1966 (DCSO records Vol. 34 Page(s) 14291-92)

Point for the $\frac{1}{4}$ sec. cor. at proportionate distance; there is no remaining evidence of the original corner.
Set an Iron post, 28" long, 2 $\frac{1}{2}$ " dia., 26" in the ground, with brass cap mkd: T 29 S R 7 W
 $\frac{1}{4}$
S 21 S 22
1966

from which
A Fir 23" dia., bears N.89°E., 15 $\frac{1}{2}$ lks., mkd. $\frac{1}{4}$ S22 BT.
A Fir 7" dia., bears N.67°W., 31 $\frac{1}{2}$ lks. mkd. $\frac{1}{4}$ S21 BT.

Fd. Brass cap and 2 BTs, Oct. 1984, Howard Johnstone, M 97-54