

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6532)

- 
- Set a post cor. of secs. 9, 10, 15 and 16, from which
- A Laurel 14" dia., bears S.32½°E., 60 lks.
  - A B.Oak 12" dia., bears N.70°E., 46 lks.
  - A Red Fir 16" dia., bears N.44°E., 16 lks.
  - A Red Fir 18" dia., bears S.28°W., 9 lks.

GLO resurvey by Hans W. Thielsen, under Group #316, Surveyed, July/Aug. 1955 - (DCSO records Vol. 28 Page(s) 11767-68)

-----

Beginning at the cor. of secs. 9, 10, 15 and 16, determined at record bearing and distance from the remaining three original bearing trees:

- A Madrona 20" dia., bears S.32½°E., 60 lks. with marks SB uncovered.
- A Fir 40" dia., bears S.28°W., 9 lks. dist., marked with a healed blaze.
- A Fir 27" dia., bears N.44°W., 16 lks. dist., marked with a healed blaze.

At the cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T 29 S R 7 W
<u>S 9 S 10</u>
S 16 S 15
1955

from which new bearing trees:

- A Fir 12" dia., bears N.64½°E., 38 lks. dist., mkd. T29S R7W S10 BT.
- A Fir 18" dia., bears S.68°E., 62 lks. dist., mkd. T29S R7W S15 BT.
- A Fir 43" dia., bears S.61°45'W., 84 lks. dist., mkd. T29S R7W S16 BT.
- A Fir 36" dia., bears N.22¼°W., 24 lks. dist., marked T29S R7W S9 BT.