

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6533)

Set ¼ sec. post, from which
A Red Fir 9" dia., bears N.42°E., 27 lks. dist.
A Dogwood, 4" dia., bears S.77°W., 10 lks. dist.

A. Boyer and J. Byron, For: L.D. Lockwood - June 9, 1953 - C.S. File 41/187

Set 4" x 4" Maple post, scribed on West side, ¼ S9; on South side, T29S R7W; on East side, ¼ S10; On North side, 1581. Blazed and scribed two trees:
12" Red Fir bears S.57°W., 30.2 ft. ¼ S9 T29S R7W 1581 BT.
14" Maple bears S.32°E., 27 ft. ¼ S10 T29S R7W 1581 BT.
This corner was renewed from orig. BT - A 9" Fir bears N.42°E., 27 lks. We found a possible scribe mark on apparent old blaze. Also this places the cor. 12 ft. North of old fence and South of sec. cor. to North. In view of the fact that the South half of this section is in error and the type of work done by the orig. Surveyor, we have used the above evidence to renew the ¼ corner.

Destroyed by Cadastral Engineers, See resurvey.

GLO resurvey by Hans W. Thielsen, under Group #316, Surveyed, July/Aug. 1955 - (DCSO records Vol. 28 Page(s) 11768)

Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: ¼

S9 | S10
1955

from which

A Fir 14" dia., bears N.75½°E., 90 lks. dist., mkd. ¼ S10 BT.

A Fir 32" dia., bears N.14°W., 67 lks. dist., mkd. ¼ S9 BT

Douglas Co. Surveyors Office - Gary Langlitz; P. Earle - May 1, 1974 - C.S. File 56/51-3

Found - 1955 GLO Iron pipe with brass cap properly marked. 32" now 36" D. Fir bears N.14°W., 44.2 ft. scribing visible on healed blaze.

The NE BT is now down, scribing is visible on open blaze. (Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 29" D.Fir bears S.88°E., 62.1 ft. scribed "¼ S10 CS BT".

Note: At this time we also find the two BTs marked by Boyer and Byron in 1953, approx. 300 ft. SE of the brass cap. We examined the remains of what was said to be the NE O.B.T. and can find no evidence of any scribing.

David Edwards - For: Roseburg Resources - 1/2008 - M 155-3

Found - BLM brass cap.
31" Fir S.88°E., 62.1 ft.
6" Fir S.35°W., 5.5 ft. (no rec.)
33" For N.14°W., 44.2 ft.

Greg Lang - For: Roseburg Resources Co - April 2013 - M165-14

Found - Brass cap
Existing 35" D.Fir - 2008 rec. by D. Edwards is
[S.88°E., 62.1']
Existing 33" D.Fir - 2008 rec. by D. Edwards is
[.N14°W., 44.2']
Existing 8" D.Fir - 2008 rec. by D. Edwards is
[S.35°W., 5.5']
New - 14" D.Fir bears N.62½°E., 41.6' scribed "¼ S10 BT"