

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6534)

Set ¼ sec. post, at average dist., from which
 A W.Oak 10" dia., bears S.24°W., 40 lks.
 A B.Oak 16" dia., bears S.15°E., 125 lks. dist.

Arthur Boyer, #1581 - Wit: H.L. Northcraft; John Fletcher -
 For: Arthur Gilbert - Oct. 1958 - M 12-72

Set by proportional measurement on line between NW and SW corners of Sec. 3.
 Drove 1½" Iron pipe and scribed following trees:
 24" Fir N.19°27'E., 410.4 ft. "¼ S3 T29S R7W 1581 BT"
 24" B.Oak S.85°40'W., 446 ft. "¼ S4 T29S R7W 1581 BT"
 30" Fir N.0°40'E., 329 ft. "¼ S3 T29S R7W 1581 BT"

Fd. OK, Sept. 1980, Glenn Baughman, M 85-35

BLM resurvey by Jelley and Rogers, under Group #1044. Surveyed, Jan/April 1981 (DCSO records Vol. 43 Page(s) 16679)

The ¼ sec. cor., reestablished by proportionate measurement and recorded by Boyer in 1957, and recorded by Baughman in 1980, and is accepted as the best available evidence of the position of the original corner, monumented with an iron pipe, 1½" dia., firmly set, projecting 3" above ground, from which bearing trees mkd. by Boyer:
 A Fir 30" dia., bears N.½°E., 498 lks. dist. with healed blaze.
 A Fir 38" dia., bears N.19 ¾°E., 622 lks. dist., with healed blaze.

At the corner point
 Set an aluminum post, 28 ins. long, 2½ ins. diam., 42 ins. in the ground, the top 14" below surface of ground, directly over iron pipe, with alum. cap mkd: T 29 S R 7 W
 1/4
 S 4 S 3
 1981

from which
 An Iron post, 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears N.28°E., 308 lks. dist., with brass cap mkd: RM 1/4 S3 T29s R7W 203.17' to COR 1981 and an arrow pointing to the corner.

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An Iron post, 28" long, 2½" dia., set 25" in the ground, for a reference monument, bears N.66½°W., 130 lks. dist., with brass cap mkd. RM 1/4 S4 T29S R7W 85.45' to COR 1981 and an arrow pointing to the corner. Corner is located in open pasture land.

Fd. ok by D.Edwards, Feb. 1998 - M 128-31