

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 409100

PRIMARY CORNER DESCRIPTION No. Sec. Cor. for 33 & 34 only, T29½-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6054)

-----  
Intersect the S. bdy. of T29S R7W, 9.01 chs. N.89°40'E., from the cor. of secs. 33 and 34.  
At the Point of intersection  
Set an iron post, 3' long, 2" dia., 28" in the ground, for cor. of secs. 33 & 34, with brass cap mkd:

-----  
S33 S34  
T29½ R7W  
1924

from which

- A live Oak, 16" dia., bears S.50°E., 55 lks., mkd: T29½S R7W S34 BT.
- A Fir, 24" dia., bears S.71°W., 91 lks., mkd: T29½S R7W S33 BT.

BLM resurvey by Harvey Wofford, G. Steven Popken, & James J. Carlson, instructions dated August 29, 1974 under Group #851. Surveyed Sept. 1974/May 1976 (DCSO records Vol. 39 Page 15814)

-----  
The cor. of secs. 33 & 34 only, on the N. bdy. of T29½S R7W, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, with brass cap mkd:

-----  
S33 S34  
T29½ R7W  
1924

from which the orig. bearing trees

- A live Oak, 22" dia., bears S.50°E., 55 lks., with healed blaze.
- A Fir, 26" dia., bears S.71°W., 91 lks., with healed blaze.