

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 34 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6521)

-----

Set ¼ sec. post, at proper distance, from which  
A Laurel 12" dia., bears S.75°W., 50 lks. dist.  
A Laurel 20" dia., bears N.55°W., 8 lks.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 6043)

-----

Intersect the point for ¼ sec. cor., located by measurement from the original bearing trees.  
At the exact cor. point  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 34 only, with brass cap mkd: ¼ S34  
1924

from which the original bearing trees:  
A Laurel 20" dia., bears S.81°W., 50 lks. dist., (not S.75°W.), plainly marked overgrowth shows this tree marked 70 years.  
A Laurel 36" dia., bears N.15°W., (not N.55°W.) blazes are plain, not opened.

New bearing trees:  
A Fir 7" dia., bears N.79°E., 29 lks. dist., mkd ¼ S34 BT.  
A Fir 7" dia., bears N.60°W., 3 lks. dist., mkd. ¼ S34 BT.  
This ¼ sec. cor. is on top of ridge, bears NE and SW.

Corner tied in BLM survey by Wofford, Popken and Carlson, under Group #851, Surveyed, 1974-76 (DCSO records, Vol. 39 Page 15814)

Corner found OK in Corrective Dependent resurvey by Jelley and Rogers, under Group #851. Surveyed, Jan. 1981 DCSO records, Vol. 42 Pages 16425-26)