

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 22 and 27

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6531)

Set ¼ sec. post, at average distance, from which
A Red Fir 10" dia., bears S.45°W., 28 lks.
A Red Fir 8" dia., bears N.25°W., 10 lks.

W. F. Briggs - 1897 - Field Book 2 Page 25

Set post marked ¼ S. Original BT gone.
Made New BT:
Red Fir 24" dia., S.66°E., 31 lks.
W.Fir 8" dia., N.78°W., 63 lks.

Marvin Ramsey - For: J.H. Baxter & Co. - July 20, 1959 - C.S. File 51/32

Determined the corner point from the only extant original bearing tree:
A D.Fir snag 20" dia., bears S.45°W., 28 lks.
Set an I.P. 3 ft. long 1½" dia., 28" in the ground mkd: RS404
Mark new BTs:
8" W.Fir bears S.68½°W., 29 lks dist., mkd. ¼ S27 RS404 BT
18" D.Fir bears N.57°W., 30 lks dist., mkd. ¼ S22 RS404 BT

Fd. I.P. & 3 BTs, Oct. 1984, Howard Johnstone, M 97-54
Fd. Ok by L. Herzstein, April 1987 M104-13 & C.S. 63/56-1A&B
Found OK by W. Rogers, Oct. 2001 - M139-3