

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for sec. 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Bruce Rogers, Deputy - For: C & D Lumber Co. - April 20, 1965 - C.S. File 54/2 & M 29-48  
-----

Set Brass cap at center ¼ cor. mkd: County Surveyors Office  
Center of Sec. 15  
T29S R7W  
1965

New BTs -13" D.Fir S.35°E., 172.5 ft. mkd. C S15 CS BT.  
15" D.Fir S.17°E., 158.2 ft. mkd. C S15 CS BT.  
The position for the center ¼ cor. determined after running a closed traverse, beginning at the N¼ cor. to the S¼ cor. to the E¼ cor., to the W¼ corner and back to the N¼ Corner.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - G.E. Quibell; K. Mosley - March 3, 1981 - C.S. File 61/19-10  
-----

Found - 13" D.Fir now a dead standing snag, bears S.35°E., 172.5 ft. Tree has a partially healed blaze with scribing visible "CS 15 CS"  
15" D.Fir now a stump, bears S.17°E., 158.2 ft. scribing visible "BT" on an unhealed blaze.  
Brass cap monument set in 1965 not found.  
Set a 1" x 36" I.P. with brass cap attached at corner position. Cap is stamped: Douglas County Surveyor  
T 29 S R 7 W  
C 1/4 S15  
1981

New BTs -4" Fir blazed "X", bears S.79½°W., 4.4 ft.  
9" D.Fir scribed "C ¼ S15 CS BT" on a double blaze bears N.34½°E., 64.0 ft.  
10" Pine scribed "C ¼ S15 CS BT" on a double blaze bears N.27½°W., 93.1 ft.  
No other trees in area suitable for scribing.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22751)  
-----

The center ¼ sec. cor. of sec. 15, established by Rogers, in 1965, perpetuated by Monrean, in 1981, and is accepted as the cor., monumented with an iron post, 1¼" dia., firmly set, projecting 4" dia., with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Rogers  
A fir snag, 15" dia., bears S.35¼°E., 172.5 ft., with fragmentary scribe marks visible on a partially healed blaze.  
A decayed fir stump, size indeterminate, bears S.17¼°E., 158.3 ft., with no marks visible. continued next page

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 440440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for sec. 15

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and the remains of bearing trees mkd. by Monrean  
A fir, 24" dia., bears N.37 $\frac{3}{4}$ °E., 63.9 ft., with a healed blaze.  
A fir, 13" dia., bears S.82 $\frac{3}{4}$ °W., 4.4 ft., with a healed double blaze.  
A pine snag, 14" dia., bears N.27 $\frac{1}{2}$ °W., 93.1 ft., with scribe marks C 4 5 and other fragmentary scribe marks visible on a partially healed blaze.  
Corner is located on a N. slope.