

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Pages 6532-33)</p> <p>-----</p> <p>Set ¼ sec. post, at average distance, from which A B.Oak 8" dia., bears S.80°E., 90 lks. dist. A B.Oak 9" dia., bears N.70°W., 30 lks. dist.</p>
<p>A. R. Evans, For: Nyberg Lumber Co. - July 7, 1953 - Wit: R.C. Grant - C.S. File 41/250 (also see C.S. File 49/4)</p> <p>-----</p> <p>Renewed from O.B.T., stump, Oak, N.70°W., 30 lks. New BTs -10" Fir S.65°W., 3.1 ft. 8" Fir N.35°W., 12.3 ft. Set Cedar Stake for corner.</p>
<p>GLO resurvey by Hans W. Thielsen under Group #346, Surveyed 1957 - (DCSO records Vol. 28 Page(s) 12158)</p> <p>-----</p> <p>Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: T29S R7W ¼ S 10 S 15 1957</p> <p>from which A Fir 30" dia., bears N.36½°W., 54 lks., mkd. ¼ S10 BT. A Fir 38" dia., bears S.72°E., 38 lks., mkd. ¼ S15 BT.</p>
<p>BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22750)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 10 & 15, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Thielsen in 1957 A fir, 41" dia., bears S.72°E., 25.1 ft., with a healed blaze and axe marks visible on bark. A sawed fir stump, 38" dia., bears N.36½°W., 35.6 ft., with a healed blaze. and a new bearing tree A fir, 5" dia., bears N.25½°E., 9.1 ft., mkd. X BT.</p>
<p>continued next page</p>

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Greg Lang - For: Roseburg Resources Co - April 2013 - M165-14

Found - Brass cap
Existing 40" D.Fir bears S.72 $\frac{3}{4}$ °E., 23.1' [2009 record per BLM is S.72°E., 25.1']
Existing 6" W.Fir bears N.25 $\frac{1}{4}$ °E., 9.2' [2009 record per BLM is [N.25 $\frac{1}{2}$ °E., 9.1']
New - 6" D.Fir bears N.31 $\frac{1}{2}$ °W., 19.1' scribed "¼ S10 BT"
26" D.Fir bears S.87 $\frac{1}{2}$ °W., 72.0' scribed "¼ S15 BT"