

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 3; & 34 of T28-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original, Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5748)

Set ¼ sec. post at proper distance, from which
A W.Oak 10" dia., bears S.23°W., 89 lks. dist.
A W.Oak 12" dia., bears N.83°E., 74 lks. dist.
Elizah Croseton's house, N.43°E.

Arthur Boyer, For: A. Gilbert - Oct. 1958 - M 12-72

Set on line at mid-point bet. cors. ½ mi. to E & W.
Drove Cedar post & buried rock 4 x 8 x 10 and scribed:
48" Oak N.32°E., 254 ft. "¼ S34 T28S R7W 1581 BT".
15" forked W.Oak S.80°E., 294 ft. "¼ S3 T28S R7W 1581 BT"
10" W.Oak on an E & W fence line N.58°W., 386 ft. "¼ S34
T28S R7W 1581 BT".

William Ruppert - for: David Stiner - Oct. 1978 - M 73-73

Found - Boyer's ¼ corner, mound of 4 or 5 rocks, one being approx. 4" x 8" x 10" & the remains of a cedar post.
Oak near E-W fence with good scar, N.41°15'W., 386.5 ft.
53" B.Oak with visible "B.T.", N.60°30'E., 257.7 ft.
W.Oak with good scar, S.78°10'E., 293.9 ft.
Set - 3/4" Rod at Boyer's Corner.

BLM resurvey by Jelley & Rogers, Group #1044. Survey, Jan./ April 1981 (DCSO records, Vol. 43 Pages 16663-64)

The 1/4 cor. reestablished by Boyer, 1957; perpetuated & recorded by Ruppert, 1978; recorded by G.Baughman, 1980; and is accepted as the best available evidence of the position of the original cor. monumented with an iron rod, 3/4" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Boyer:

- An Oak 50" dia., bears N.32°E., 383 lks. dist., with illegible scribe marks visible on bark blaze.
- An Oak 50" dia., bears N.59°E., 388 lks., with scribe marks BT visible on partially healed blaze.
- An Oak 16" dia., bears S.79½°E., 445 lks. with healed blaze.
- An Oak 20" dia., bears N.42 3/4°W., 583 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 38 ins. in the ground, directly over iron rod, the top 10" below the surface

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 3; & 34 of T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

of the ground, with brass cap mkd. T 28 S R 7 W
1/4 $\frac{S\ 34}{S\ 3}$
T 29 S
1981

Corner is located in open pasture land.