

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 451100

PRIMARY CORNER DESCRIPTION No. ¼ cor. for Sec. 34 only, T29½-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Mensch under Instructions dated April 18, 1924
(DCSO records Vol. 14 Page(s) 6044)

Point for ¼ sec. cor. of sec. 34 only, T29½S R7W, later
determined.

Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for
¼ sec. cor. of sec. 34, T29½S R7W., only with brass cap mkd:

¼ S34
T29½
1924

from which

A Laurel 44" dia., bears S.3°E., 62 lks. dist., marked ¼
S34 T29½ BT.

A Laurel 46" dia., bears S.54°W., 58 lks. dist., marked ¼
S34 T29½ BT.

BLM survey by Wofford, Popken and Carlson, under Group #851.
Surveyed Sept. 1974/May 1976 (DCSO records Vol. 39 Page(s)
15813-14)

True point for the ¼ sec. cor. of sec. 34 only, on the N.
bdy. of T29½S R7W.

Set an iron post 28" long, 2½" dia., 22" in the ground, with
brass cap mkd:

¼ S 34
T 29½ S R 7 W
1976

from which

A Pine 34" dia., bears S.72½°E., 29 lks. dist., mkd. ¼ S34
BT.

From this point, the orig. ¼ sec. cor. of sec. 34, bears
South, 0.084 chs. dist., monumented with an iron post, 1"
dia., firmly set, projecting 8" above ground, with brass cap
marked:

¼ S 34
1924
T 29½

from which the original bearing trees:

A Madrone 46" dia., bears S.3°E., 62 lks. dist., with
healed blaze.

A Madrone 62" dia., bears S.54°W., 61 lks. dist., with
healed blaze.

I add marks AM 1976.

(Cont. Next Page)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Howard Johnstone, For: Roseburg Lumber Co. - July 30, 1980 -
M 84-80 and C.S. File 58/214-2

Found - 1924 GLO brass cap and iron pipe mkd. "AM 1976".
1976 Cadastral brass cap and iron pipe bears
N.5°52'33"W., 5.23 ft.
Set 5/8" x 40" I.R. and al. cap 8.69 ft. South of 1924 BC/IP.
New BTs -36" Pine, N.66°E., 19.0 ft.
66" Madrone S.66°W., 35.0 ft.

Howard Johnstone, For: Roseburg Lumber Co. - Jan. 22, 1981 -
C.S. File 58/229-7

Scribed new bearing tree for North ¼ corner, Sec. 34, T29½S
R7W because new road construction will eliminate O.B.T., 66"
madrone, S.66°W., 35.0 ft.
Found - 1924 GLO BC/IP marked "AM 1976".
Our 5/8" x 40" I.R. and alum. cap 8.69 ft. South of
BC and on true line.
36" Pine, N.66°E., 19.0 ft.
66" madrone S.66°W., 35.0 ft.
New BT - 11" D.Fir S.56°E., 60.2 ft. from alum. cap (S.48°E.,
64.6 ft. from GLO brass cap.

BLM Corrective dependent resurvey by Jelley and Rogers, under
Group #851, Surveyed, Jan. 1981 (DCSO records Vol. 42 Page(s)
16425)

The ¼ sec. cor. of sec. 34 only, on the N. bdy. of T29½S R7W,
established and recorded by Howard Johnstone in 1980, and is
accepted as the corner, monumented with an iron rod, 5/8"
dia., firmly set, projecting 10" above ground with an alum.
cap 2" dia., mkd.: T 29 ½ S R 7 W S34 ONLY

N 1/4
1980
LS 498

from which a bearing tree mkd. by Johnstone:
A Fir 10" dia., bears S.60°E., 91 lks. dist., with scribe
marks ¼ S34 BT visible on open blaze.
and a new bearing tree:
A Fir 18" dia., bears S.75°W., 132 lks. mkd. ¼ S34
BT.

From this point, the orig. ¼ sec. cor. of sec. 34 bears
North, 0.131 chs. dist., monumented with an iron post, 1"
dia., firmly set, projecting 8" above ground, with brass cap
marked:

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 451100

PRIMARY CORNER DESCRIPTION No. ¼ Cor. for Sec. 34 only, T29½-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

AM
 ¼ S 34
 T 29 ½ S
 1976
 1924

from which the original bearing trees:

A Madrone 50" dia., bears S.3°E., 62 lks. dist., with healed blaze.

A madrone 64" dia., bears S.54°W., 61 lks. dist., with healed blaze.

From this same point, the ¼ sec. cor. of sec. 34 only, erroneously established by Wofford, Popken and Carlson, in 1974-76, bears N.2°12'W., 0.208 chs. dist., monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, mkd. and witnessed as described in the official record.

I remove the iron post and destroy the marks on the bearing trees.