

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6523)

Set ¼ sec. post, from which
A Red Fir 4" dia., bears N.75°E., 11 lks.
A B.Oak 6" dia., bears S.60°W., 19 lks.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5967)

Intersect the point for ¼ sec. cor., located by measurement from the original bearing trees.

At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec.cor. of Sec. 34 only, with brass cap mkd: ¼S34|
1924

from which (the original bearing trees)
A hollow B.Oak stump, 8" dia., bears S.58°W., 19 lks. (not S.60°W.) marks plain inside overgrowth.
A Fir 8" dia., bears N.75°E., 11 lks. dist., marks plain on the bark.

New Bearing trees:
A Fir 36" dia., bears S.30°W., 22 lks. dist., marked ¼ S34 BT.
A Fir 16" dia., bears N.32°W., 10 lks. dist., mkd. ¼ S34 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - April/May 1962 - C.S. File 49/139-56

Found - GLO brass cap at corner and NW BT. SW BT, now down.
New BT - 18" R.Fir bears N.87°E., 7.5 ft. scribed S34½ CS BT.