

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 500173

PRIMARY CORNER DESCRIPTION Cor. for Secs. 26½ & 34½ only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Mensch under Instructions dated April 18, 1924
(DCSO records Vol. 14 Page(s) 5966-67)

Intersect the line bet. secs. 36½ and 34½., West 7.04 chs.
from Campbell's closing cor. of secs.26 and 35.

At the point of intersection

Set an Iron post, 3 ft. long, 2" dia., 28" in the ground, for
cor. of secs. 26½ and 34½, with brass cap marked:

T29S
|
S34 — 26½
|
S34½
|
R7W
1924

from which

A Fir 12" dia., bears N.43°E., 50 lks. dist., marked T29S
R7W S26½ BT.

A Fir 12" dia., bears S.42°E., 32 lks. dist., marked T29S
R7W S34½ BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John
Powell; Dale McFarland - May 1962 - C.S. File 49/139-57

Found - Brass cap at corner and both BTs, now snags.

New BTs -24" R.Fir bears N.40°E., 52.0 ft. scribed S26½, T29S
R7W CS BT.

24" R.Fir bears S.44°E., 26.2 ft. scribed S34½ T29S
R7W CS BT.