

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27 and 34 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6523)

-
- Set post, cor. of secs. 26, 27, 34 and 35, from which
- A Red Fir 4" dia., bears N.50°W., 9 lks. dist.
 - A Red Fir 6" dia., bears N.25°E., 34 lks. dist.
 - A Maple 4" dia., bears S.5°E., 18 lks. dist.
 - A Red Fir 8" dia., bears S.33°W., 32 lks. dist.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5966)

Intersect the point for Ford's cor. of secs. 26, 27, 34 and 35, located by measurement from the old original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 27 and 34 only, with brass cap marked:

T29S
S27 S26½
S34
R7W
1924

from which (the original bearing trees)

- A Fir 24" dia., bears S.33°W., 32 lks. dist., overgrowth 70 years old, marks plain after removal.
- A Fir stump 10" dia., bears N.50°W., 9 lks. dist., marks are plain on overgrowth.
- A Fir stump hole, bears N.25°E., 34 lks. dist.
- Old SE tree entirely destroyed.

New Bearing trees:

- A Fir 30" dia., bears S.85°W., 18 lks. dist., marked T29S R7W S34 BT.
- A Fir 36" dia., bears N.57°W., 52 lks. dist., marked T29S R7W S27 BT.

Cor. Fd. OK, BLM resurvey by Wofford; Popken; and Carlson - 1974-76 (DCSO records Vol. 39 Page(s) 15819)