


TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 500277

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 23 & NW Cor. Sec. 26½

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Mensch under Instructions dated April 18, 1924
(DCSO records Vol. 14 Page(s) 5969-70)

Point for cor. of secs. 23 and 26½ on prolongation of the S.
bdy. of Sec. 23, Campbell's survey; 7.21 chs. West from
Campbell's closing cor. of secs. 23 and 26.
Set an iron post 3 ft. long 2" dia., 28" in the ground, for
cor. of secs. 23 and 26½ on E. bdy. of sec. 27, with brass
cap marked:



from which

A Fir 16" dia., bears N.30½°E., 183 lks. dist. marked T29S
R7W S23 BT.

A Fir 6" dia., bears S.45°E., 249 lks. dist., marked T29S
R7W S26½ BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale
McFarland; John Powell - May 1962 - C.S. File 49/139-62

Found - GLO brass cap at cor. and SE BT., shows scar. We do
not open.

Did not find NE bearing tree.

New BTs -15" Cedar bears S.84°E., 33.4 ft. scribed S26½ T29S
R7W CS BT.

6" R.Fir bears N.36°E., 43.3 ft. scribed S26 CS BT.

NW corner of old house bears East 5.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike
Darby; J. Halterman - Nov. 27, 1963 - C.S. File 49/139-108

Found - 1924 GLO brass cap at corner.

All BTs, now dead, burned at the time house burned.

New BTs -Cedar bears S.73°E., 70.0 ft. scribed S26½ T29S R7W
CS BT.

7" Pine bears N.59°E., 83.0 ft. scribed S23 CS BT.

BLM resurvey by Jelley and Rogers, under Group #1044 -
Surveyed Jan/April, 1981 - (DCSO records Vol. 43 Page(s)
16668-69)

True point for the cor. of secs. 23 and 26½ only.

Set an alum. post, 28" long, 2½" dia., 24" in the ground,
with alum. cap mkd:

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 500277

PRIMARY CORNER DESCRIPTION Sec. cor. for 23 and 26½ only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 29 S R 7 W
S27 | S 23
 | S 26½
 1981

from which

A Fir 14" dia., bears N.75°E., 98 lks. dist., mkd. T29S R7W S23 BT.

A Fir 8" dia., bears S.71½°E., 81 lks. dist., mkd. T29S R7W S26½ BT.

From this point, the original cor. of secs. 23 and 26½ only, bears S.89°56'W., 0.03 chs. dist., perpetuated and recorded by James Byron, in 1962 and 1963, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with 1924 marked brass cap.

from which an original bearing tree

A Fir 24" dia., bears S.45°E., 249 lks. dist., with healed blaze.

and bearing trees mkd. by Byron in 1962

A Fir 17" dia., bears N.38°E., 65 lks. dist., with healed blaze.

A twin Cedar 24" dia., bears S.83½°E., 51 lks. dist., with scribe marks T29S R7W S2 CS BT visible on partially healed blaze.

and bearing trees mkd. by Byron in 1963

A Pine 9" dia., bears N.59°E., 126 lks. dist., with illegible scribe marks visible on partially healed blaze.

A Cedar 30" dia., bears S.71°E., 105 lks. dist., with healed blaze.

I ADD MARKS AM TO BRASS CAP.