

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION East ¼ cor. for Sec. 22 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Mensch under Instructions dated April 18, 1924
(DCSO records Vol. 14 Page(s) 5971)

(Note: In Vol. 14 Pg. 5943, Mensch looked for and could not find Ford's ¼ cor. for 22 and 23)

Proportionate distance.

Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 22 only with brass cap marked:

¼ S22 |
1924

from which

A Fir 16" dia., bears S.23°W., 72 lks. dist., mkd. S22 BT

A Fir 10" dia., bears N.56°W., 42 lks. mkd. ¼ S22 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - June 1962 - C.S. File 49/139-75

Found - Brass cap set in 1924 and BTs as follows:

16" Fir S.23°W., 72 ft. (stump)

10" Fir N.56°W., 42 ft. (windfall, scribing visible)

New BTs - 7" W.Fir N.71°W., 27.6 ft. mkd. E ¼ S22 CS BT.

14" D.Fir, South, 28.5 ft. mkd. E ¼ S22 CS BT.

Fd. Brass cap and 3 BTs - BLM resurvey by Jelley and Rogers, 1981 - DCSO records, Vol. 43 Pg. 16670

Fd. OK, Oct. 1984, Howard Johnstone, M 97-54

Fd. Ok by L. Herzstein, April 1987 M104-13 & C.S. 63/56-1A&B

Found OK by W. Rogers, Oct. 2001 - M139-3