

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6524)

-
- Set a post, cor. of secs. 14, 15, 22 and 23, from which
- A Laurel 15" dia., bears S.35°E., 17 lks.
 - A Laurel 4" dia., bears S.86°W., 70 lks.
 - A Laurel 6" dia., bears N.55°W., 50 lks.
 - A Laurel 18" dia., bears N.80°E., 28 lks.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5972)

Intersect the point for cor., located by measurement from the original bearing trees, on which the blazes and marks are plain.

At the exact cor. point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap marked:

T29S R7W
S15 S14
S22 S23
1924

from which the original bearing trees:

- A Laurel 40" dia., bears N.70°E., 28 lks. (Not N.80°E)
- A Laurel 30" dia., bears S.42°E., 17 lks. (not S.35°E.)
- A Laurel stump bears S.80°W., 50 lks. (not S.86°W)
- A Laurel 20" dia., bears N.64°W., 50 lks. (not N.55°W)

New Bearing trees:

- A B.Oak 12" dia., bears N.60°E., 37 lks. dist., mkd. T29S R7W S14 BT.
- A Fir 12" dia., bears S.12°E., 31 lks. dist., mkd. T29S R7W S23 BT.
- A Fir 18" dia., bears S.11°W., 26 lks. dist., mkd. T29S R7W S22 BT.
- A Pine 30" dia., bears N.7°W., 53 lks. dist., mkd. T29S R7W S15 BT.

Corner Fd. OK, BLM resurvey by Jelley & Rogers, 1981 (DCSO records, Vol. 43 Pg. 16671)

Fd. OK, April 1991, M 113-6