

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6528)

Set 1/4 sec. post, from which
A W.Oak 20" dia., bears S.50°W., 100 lks.
A B.Oak 4" dia., bears S.30°E., 50 lks.

R. C. Grant - Wit: A.R. Evans; William Hart - July 7, 1953 - C.S. File 41/250

Set from O.B.T., which is 23" Oak, S.50°W., 66.0 ft.
New BT - 13" Fir S.24°E., 20.8 ft.
Set 4" x 4" Cedar stake.

GLO resurvey by Hans W. Thielsen under Group #346 - Surveyed, April/May 1957 (DCSO records Vol. 28 Page(s) 12152-53)

The 1/4 sec. cor., determined at record bearing and distance from the only remaining original bearing tree:
A W.Oak 12" dia., bears S.50°W., 100 lks. dist., with partial scribe marks visible on opened blaze.

At the cor. point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:
T29S R7W
1/4
S 10*S 11
1957

from which new bearing trees:
A Fir 30" dia., bears S.40 1/2°E., 75 lks. dist., mkd. 1/4 S11 BT.
A Fir 12" dia., bears N.43°W., 141 lks. mkd. 1/4 S10 BT.

BLM resurvey by Wayne L. Rogers, under Group #1208 - Surveyed, Aug. 1984/Jan. 1985 (DCSO records Vol. 47 Page(s) 17983)

The 1/4 sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap mkd.

T 29 S R 7 W
1/4
S 10 * S 11
1957

from which remains of an original bearing tree
An Oak snag 24" dia., bears S.50°W., 100 lks. dist., with fragmentary reverse scribe marks visible on opened blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of bearing trees mkd. by Thielsen
A Fir 31" dia., bears S.49½°E., 75 lks., with healed blaze
A Fir snag 11" dia., bears N.43°W., 141 lks., with scribe
marks ¼ S10 BT visible on open blaze.
and a new bearing tree
A Fir 6" dia., bears N.23°W., 31 lks., mkd. ¼ S10 BT.
Corner is located in a barb wire fence, extending N. and S.

Greg Lang - For: Roseburg Resources Co - April 2013 - M165-14

Found - Brass cap
Existing 32" D.Fir - 1984 record by BLM is
[S.49½°E., 49.5']
Existing 12" D.Fir - 1984 record by BLM is [N.23°W.,
20.46']
New - 17" D.Fir bears N.48¼°E., 45.7' scribed "¼ S11 BT"
14" D.Fir bears S.49¼°W., 46.55' scribed "¼ S10 BT"