

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 2 and 3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6529)

-----  
Set a ¼ sec. post, at proper distance, from which  
A B.Oak 12" dia., bears S.75°E., 55 lks.  
A Laurel 15" dia., bears N.35°W., 62 lks. dist.

-----  
Glenn S. Baughman, LS #536 - For: Douglas County Lumber Co. - Aug. 1980 - C.S. File 58/144 and M 85-35

-----  
Set 1" x 36" Iron pipe with brass cap mkd: T29S R7W 1/4 S3 S2 1980 RLS 536.  
BTs - 10" Fir bears N.35°W., 30.0 ft. scribed ¼ S3 BT.  
30" Madrone bears S.62°E., 61.3 ft. scribed ¼ S2 BT.

-----  
See Corner Visit by DCSO, March 5, 1981 For: Koopman. C.S. File 61/19-13 & (5/20/1982) C.S. File 61/19-66

-----  
BLM resurvey by Jelley and Rogers, under Group #1044, Surveyed, Jan/April 1981 (DCSO records Vol. 43 Page(s) 16674-75)

-----  
The ¼ sec. cor., reestablished by proportionate measurement and recorded by Glenn Baughman in 1980, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground with properly mkd. brass cap. from which the bearing trees mkd. by Baughman  
A Madrone 31" dia., bears S.59½°E., 93 lks. dist, with scribe marks ¼ S2 BT visible on open blaze.  
A Fir 11" dia., bears N.34 3/4°W., 44 lks. dist., with scribe marks ¼ S3 BT visible on open blaze.  
From this point, United States Coast and Geodetic Survey triangulation station "TWO OAKS 1942" bears S.86°28'E., 117.27 chs. dist.