

PRIMARY CORNER DESCRIPTION SE Sec. Cor. for 34½ only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 6045)

Intersect the W. bdy. of sec. 35, T29S R7W, as surveyed by Campbell, 17.04 chs. N.0°34'W. from the cor. of secs. 2, 3, 34 and 35, established by Byars.

At the point of intersection

Set an iron post 3 ft. long, 3" dia., 27" in the ground, for NE cor. of T29½S R7W with brass cap mkd:

T29SR7W  
S34½ S35  
S34  
T29½S  
R7W  
1924

from which

A Fir 8" dia., bears S.43°W., 4 lks. dist., mkd. T29½S R7W S34 BT.

A Fir 14" dia., bears N.19°W., 17 lks. dist., mkd. T29S R7W S34½ BT.

BLM resurvey by Wofford, Popken and Carlson, under Group #851. Surveyed, Sept. 1974/May 1976 - (DCSO records Vol. 39 Page(s) 15812)

Beginning at the true point for the NE cor. of Tp. 29½S., R7W, and cor. of sec. 34½, T29S R7W, on the W. bdy. of sec. 35, T29S R7W.

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd:

T 29 S R 7 W  
S 34½ S 35  
S 34  
T 29½ S  
1976

from which

A Fir 15" dia., bears S.79½°W., 58 lks. dist., mkd. T29½S R7W S34 BT.

A Fir 12" dia., bears N.36°W., 18½ lks. dist., mkd. T29S R7W S34½ BT.

From this point, the orig. NE cor. of T29½S R7W, and cor. of 34½, T29S R7W, bears S.89°28'E., 0.12 chs. dist. monumented with an iron post, 3" diam., firmly set, projecting 18" above ground, with brass cap mkd:

T 29 S R 7 W  
S 34½ S 35  
S 34  
T 29½ S  
R 7 W  
1924

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 507119

PRIMARY CORNER DESCRIPTION SE Cor for Sec. 34½ only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the original bearing trees  
A Fir 15" dia. bears S.43°W., 4 lks. dist., with healed  
blaze.  
A Fir 15" dia., bears N.19°W., 17 lks. dist., with healed  
blaze.  
I ADD MARKS AM 1976