

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 507140

PRIMARY CORNER DESCRIPTION ¼ cor. to secs. 34½ & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCS0 Vol. 14 Page 5979-80)

Set an iron post, 3 ft. long, 1" diam., 28" in the ground, for ¼ sec. cor., with brass cap marked

¼
S34½ | S35
1924

from which:

- A fir, 6" diam., bears S.55°E., 17 lks., mkd. ¼ S35 BT.
- A fir, 12" diam., bears N.25°W., 48 lks., mkd. ¼ S34½ BT.

James W. Byron, Dep. Co. Surveyor - John Powell & Dale McFarland - Apr/May 1962 - C.S. 49/139-56

Found- GLO Brass cap at cor. & SE. BT. No trace of NW. BT.

New BT- 38" R.Fir, bears S.49°W., 13.5 ft., (bark scribed ¼ S34½ CS) wood scribed "BT".

FD. Ok. - BLM resurvey by Harvey Wofford, G. Steven Popken, & James J. Carlson, Surveyed Sept. 1974/May 1976 (DCS0 records Vol. 39 Page 15818)

See M164-66 by David Edwards 2/2013