

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 507240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 26½ only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Mensch under Instructions dated April 18, 1924
(DCSO records Vol. 14 Page(s) 5977-78)

Proportionate distance.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for
¼ sec. cor., with brass cap marked:

¼
S26½ | S26
1924

from which

A Fir 20" dia., bears N.29°E., 38 lks. dist. mkd. ¼ S26 BT
A Fir 14" dia., bers N.61°W., 12 lks. dist., mkd. ¼ S26½
BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John
Powell; Dale McFarland - May 1962 - C.S. File 49/139-62

Found - Both 1924 BTs., down. We open and find good
scribing "2" on NE BT.

Set brass cap at cor. mkd: County Surveyors Office, 1962

¼ S26½ | S26 T29S R7W

New BTs -9" Cedar bears S.12°W., 6.0 ft. scribed ¼ S26½ CSBT
18" W.Fir bears N.12°E., 28.1 ft. scribed ¼ S26 CSBT