

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26 and 26½

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Roy T. Campbell under Contract #789 dated Aug. 21, 1909 - (DCSO records Vol. 16 Page(s) 6565-66)

-----  
At the point of intersection with the N. and S. line, I set a basalt stone, 15 x 10 x 10", 10" in the ground, for C.C. for secs. 23 and 26, marked C.C. on E. with 2 grooves on S. and E. faces, from which

A Fir 10" dia., bears N.62°30'E., 121 lks. dist., mkd. T29S R7W S23 BT.

A Fir 24" dia., bears S.84°48'E., 66 lks. dist., mkd. T29S R7W S26 BT.

GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 5975-76)

-----  
I commence at Campbell's closing cor. of secs. 23 and 26, which is a basalt stone, 15x12x10 ins. marked CC on E., with 2 grooves on S. and E. faces; from which (the original bearing trees)

A Fir 10" dia., bears N.52½°E., 121 lks. dist. mkd. T29S R7W S23 BT.

A Fir 24" dia., bears S.84 3/4°E., 66 lks. dist., mkd. T29S R7W S26 BT.

I change this cor. to cor. of secs. 26 and 26½; obliterate marks on the cor. and reset same 10" in the ground, marked S26 on SE. and S26½ on SW. face; from which

New Bearing trees:

A Fir 5" dia., bears S.7°W., 13 lks. dist., marked T29S R7W S26½ BT.

A Fir 12" dia., bears N.8°W., 72 lks. dist., marked T29S R7W S23 BT.

From this corner, the cor. erroneously reported by Campbell as the Ford cor. of secs. 22, 23, 26 and 27, and restored by him as cor. of secs. 22 and 27, bears North, 2.03 chs. dist. This cor. is a basalt stone, 5x12x10 ins. above ground, marked and witnesses as described by Campbell. I change this cor. to witness point, obliterate the marks on cor. and bearing trees and remark the cor. W P and the bearing trees W P B T.

(Campbell's survey notes, DCSO records, Vol. 16 Pg. 6565)

Douglas Co. Surveyors Office - Ben B. Irving - Wit: N.E. Richardson - July 30, 1938 (no record source found, see "old" corner book, Pg. 175)

-----  
Found - A rock as described in the Govt. field notes.  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 26 and 26½ only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

One bearing tree has been destroyed by fire. The other is down and rotting.

Marked new BTs -  
 Cedar 8" dia., bears S.15°W., 25 lks. blazed and scribed T29S R7W S26½ CS BT.  
 A Fir 8" dia., bears S.20°E., 22 lks. blazed and scribed T29S R7W S26 CS BT.

---

BLM resurvey by Jelley and Rogers, under Group #1044 - Surveyed Jan/April 1981 - (DCSO records Vol. 43 Page(s) 16667-68)

-----

The cor. of secs. 26 and 26½ only, perpetuated and recorded by Irving in 1938, monumented with the original basalt stone, 9 x 6 x 6 ins. (Rec. 15 x 12 x 10), firmly set, projecting 5" above ground, mkd. with 2 notches and s26 on SE., and 2 notches and S26½ on SW. faces, alongside of which is an iron pipe, 1½" dia., firmly set, projecting 6" above ground, from which the remains of an original bearing tree:  
 A sawed Fir stump size indeterminate, bears S.84 3/4°E., 66 lks. dist., with scribe marks T2 R7 S26 BT visible on open blaze.  
 and bearing trees mkd. by Irving  
 A grand Fir 12" dia., bears S.16°E., 22½ lks. dist., with healed blaze.  
 A cedar 10" dia., bears S.19½°W., 24 lks. dist., with healed blaze.

At the corner point  
 Set an alum. post, 28" long 2½" dia., 24" in the ground with alum. cap mkd:

T 29 S R 7 W	
T 23	
S 26 ½	S 26
1981	

From this point, the corner erroneously reported by Campbell as the Ford cor. of secs. 22, 23, 26 and 27, restored by him as the cor. of secs. 22 and 27 only, and changed to a witness point by Mensch, bears N.0°36'E., 2.03 chs. dist., determined at record bearing and distance from bearing trees by Campbell:  
 A Fir 35" dia., bears S.35½°W., 30 lks. with healed blaze.  
 A Fir 34" dia., bears N.31½°W., 24 lks. with healed blaze.  
 (Campbell's notes in DCSO records, Vol. 16 Pg. 6565)

---

Douglas Co. Surveyors Office - Larry E. Monrean, deputy - T.L. Buley - Oct. 6, 1981 - C.S. File 61/29-4

-----

(Cont. Next Page)

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 507300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26 and 26½ only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Found - An unrecorded I.P. w/alum. cap. BLM monument firmly in place; cap is stamped: T29S R7W S23 S26½ S26 1981. (See above notes for 1981 BLM survey)  
Along southeast edge of BLM monument, is stone buried nearly flush with ground. The stone measures 6½" x 7" across the top. Top of stone is marked: S26½; East face has 2 notches.  
No orig. or 1924 BTs were found.  
8" Cedar with well-healed double blaze bears S.18°W., 16.1 ft. (Rec. S.15°W., 16.5 ft.)  
8" now 14" Fir with well healed double blaze bears S.17½°W., 14.5 ft. (Rec. S.20°E.)  
New BTs -12" Fir scribed "T29S R7W S26 CS BT" on a double blaze, bears S.54°E., 11.2 ft.  
8" Fir scribed "S23 CS BT" on a double blaze bears N.44½°W., 8.6 ft.  
(Bearings and distances recorded are from BLM cap position)