

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854) (DCSO records Vol. 15 Page(s) 6525)

-----  
(Common Corner)

Set ¼ sec. post, at average distance, from which

A B.Oak 10" dia., bears N.5°W., 20 lks.

A B.Oak 7" dia., bears S.35°E., 63 lks.

-----  
GLO survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 15 & 16 Page(s) 5943 & 5973)

-----  
(On page 5943, Mensch retraced the line between 14 and 23, found no trace of ¼ sec. cor.)

(Page 5973)

Proportionate distance,

Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 14 only with brass cap marked:

¼ S14  
1924

from which

A Fir 8" dia., bears N.60°E., 68 lks. dist., mkd. ¼ S14 BT

A Fir 10" dia., bears N.42°W., 51 lks. mkd. ¼ S14 BT.

-----  
Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - May 1962 - C.S. File 49/139-63

-----  
Found - 1924 GLO brass cap at cor. & orig. NE BT. NW BT gone.

New BT - 12" R.Fir N.75°W., 20.6 ft. scribed S¼ S14 CS BT

-----  
Douglas Co. Surveyors Office - Karen Reed; Frank Silagy - Feb. 14, 1979- C.S. File 60/24-10

-----  
CONDITION REPORT ONLY. NO MONUMENT OR NEW ACCESSORIES SET.

Found - A 1924 GLO brass cap properly marked, protruding 8" above ground.

An 8" D.Fir ;now 16" bears N.60°E., 44.9 ft. with well healed blaze. (1924 BT)

The NW BT is gone.

A 12" R.Fir now 15" bears N.75°W., 20.6 ft. with well healed double blaze. (1962 BT)

An unrecorded 12" Cedar bears S.68°W., 14.6 ft. marked with 9" "X" and 9" long, blaze on North and South side of tree.

-----  
Fd. OK, 1981, BLM, Jelley/Rogers, Vol. 43 Pg. 16672

Fd. OK, April 1991, M 113-6