

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 11 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Ford, 1854 (DCSO records Vol. 15 Page(s) 6528)</p> <p>-----</p> <p>Set ¼ sec. post, at average distance, from which A Laurel 12" dia., bears N.37°W., 44 lks. dist. A Laurel 6" dia., bears S.13°E., 34 lks. dist.</p>
<p>BLM resurvey by Hans Theilsen, under Group #346, Surveyed, April/May 1957 - (DCSO records Vol. 28 Page(s) 12152)</p> <p>-----</p> <p>Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: T29S R7W</p> <p style="text-align: center;">¼ <math>\frac{S 11}{S 14}</math> 1957</p> <p>from which A Fir 14" dia., bears N.72°W., 5 lks. dist., mkd. ¼ S11 BT A Fir 10" dia., bears S.9°E., 71 lks. mkd. ¼ S14 BT.</p>
<p>BLM resurvey by Hans Theilsen, under Special Instructions and Group #346 - Surveyed Aug.1959 - (DCSO records Vol. 30 Page(s) 12808)</p> <p>-----</p> <p>Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: T29S R7W</p> <p style="text-align: center;">¼ <math>\frac{S 11}{S 14}</math> 1957</p> <p>from which A Fir, 14" dia., bears N.6½°E., 6 lks. mkd. ¼ S11 BT. A Fir 8" dia., bears South, 70 lks. mkd. ¼ S14 BT.</p>
<p>Fd. OK, April, 1991, M 113-6</p>
<p>BLM Survey by Wayne L. Rogers, Under group #1208, Surveyed, Aug. 1984/Jan. 1985 - (DCSO records Vol. 47 Page(s) 17979)</p> <p>-----</p> <p>The ¼ sec. cor., monumented with an I.P. 1" dia., firmly set, projecting 12" above ground, with 1957 brass cap. from which the remains of a bearing tree mkd. by Thielsen: A root hole, bears South 70 lks. dist., with down Fir alongside, 16" dia., with healed blaze. and new bearing trees:</p> <p>(Cont. Next Page)</p>

TOWNSHIP 29 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Grand Fir 14" dia., bears S.42°W., 68 lks. dist., mkd. ¼ S14 BT.  
A Fir 4" dia., bears N.32°W., 26½ lks. dist., mkd. X BT. corner is located in the edge of a clear-cut, edge bears E. and W., timber to North.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2270, Surveyed May/Aug. 2009 - (DCSO records Vol. 57 Page(s) 22749)

-----

The ¼ sec. cor. of secs. 11 and 14, monumented with an iron post, 1" dia., firmly set, projecting 18" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Thielsen in 1957  
A roothole bears South, 46.2 ft., alongside of which is a down, decayed fir, size indeterminate, with no marks visible.  
and bearing trees mkd. by Rogers  
A fir, 20" dia., bears S.42°W., 44.9 ft., with a healed blaze.  
A fir, 13" dia., bears N.32°W., 17.5 ft., with a healed double blaze.  
Corner is located on a W. slope.