

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 2 and 11

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Original - Ford, 1854 (DCSO records Vol. 15 Page(s) 6529)</p> <p>-----</p> <p>Set ¼ sec. post, at average distance, from which</p> <p> A B.Oak 10" dia., bears S.27°E., 43 lks.</p> <p> A B.Oak 18" dia. bears N.78°E., 84 lks.</p>
<p>J.W. Cole - For:Voytilla and Parkinson Vol. 3 Pg. 171-173 - C.S. File 6/33 Oct. 1923</p> <p>-----</p> <p>I set an Oak post and a rock 6 x 6 x 12", also a gun barrel, marked ¼S CS, from which</p> <p> A Fir 18" dia., bears S.72°W., 17.2 ft.</p> <p> A Fir 12" dia., bears S.57°30'E., 22.0 ft.</p> <p>(Corner verified by Eppstein in 1927. Vol. 3 Pg. 173)</p>
<p>Theilsen, 1957 (DCSO records Vol. 28 Page(s) 12154)</p> <p>-----</p> <p>The ¼ sec. cor., remonumented by the County Surveyor in 1923 with a basalt stone, 12x6x6 ins. marked ¼ on W. face, firmly set 6" in the ground, from which bearing trees marked by the County Surveyor</p> <p> A Fir 15" dia., bears S.57½°E., 33 lks. dist., plainly blazed and healed.</p> <p> A Fir 24" dia., bears S.72°W., 26 lks. dist., marked BT on partly opened blaze.</p> <p>At the cor. point</p> <p>Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:</p> <p style="text-align: right;">T29S R7W</p> <p style="text-align: right;">¼ $\frac{S\ 2}{S\ 11}$</p> <p style="text-align: right;">1957</p> <p>from which a new bearing tree</p> <p> A Fir 12" dia., bears N.32°W., 61 lks. dist. mkd. ¼ S2 BT.</p> <p>Reset the basalt stone alongside the iron post.</p> <p>The corner falls on a spur, slopes SW.; edge of heavy timber bears N. and S.</p>
<p>BLM subd. of section 11 by Rogers in 1984 (DCSO records 47 Page 17982) found Brass cap and BTs. Also tied a triangulation point:</p> <p> United States Coast and Geodetic Survey triangulation station TWO OAKS 1942, bears N.69°02'E., 87.29 chs. dist.</p>